

Coal swelling strain and permeability change with injecting liquid/supercritical CO₂ and N₂ at stress-constrained conditions

Tamotsu Kiyama^a, Soshi Nishimoto^b, Masaji Fujioka^c, Ziqiu Xue^d, Yoji Ishijima^a, Zhejun Pan^e and Luke D. Connell^e

^a Horonobe Research Institute for the Subsurface Environment, Northern Advancement Center for Science and Technology, 5-3, Sakaemachi, Horonobe-cho, Teshio-gun, Hokkaido 098-3221, Japan

^b Nuclear Fuel Cycle Backend Research Center, Civil Engineering Research Laboratory, Central Research Institute of Electric Power Industry, 1645, Abiko, Abiko-shi, Chiba 270-1194, Japan

^c Research and Development Dept., Japan Coal Energy Center, 3-14-10, Mita, Minato-ku, Tokyo 108-0073, Japan

^d Laboratory of Engineering Geology, Department of Civil and Earth Resources Engineering, Graduate School of Engineering, Kyoto University, C-1 Cluster, KyotoDaigakuKatsura, Nishikyo-ku, Kyoto 615-8540, Japan

^e CSIRO Earth Science and Resource Engineering, Ian Wark Laboratory, Bayview Avenue, Clayton, Victoria 3168, Australia

[International Journal of Coal Geology](#)

[Volume 85, Issue 1](#), 1 January 2011, Pages 56-64